Technomad DragonFly™ PA System

Highly Portable, Self-powered, High Output, Expandable PA System



122dB SPL continuous output

Fully weatherproof

Wireless microphone built-in

Fast charging, lightweight LiFeP0 battery pack

Full Range Neodymium coaxial transducer

Lightweight - just 23 lbs.

Microphone and line level inputs

Expansion Slot for Schedulon automatic audio player, CD player, second wireless microphone or audio distribution module

Gasketed cover for mixer control surface


Integrated smart charger for battery pack



The DragonFly is a portable PA unit designed to provide high quality audio while offering Technomad's unsurpassed combination of audio quality, product flexibility and ruggedness. **Fully weatherproof**, the Dragon-Fly can easily be transported and set up by one person. A molded in stand-mount socket on the bottom of the unit and inserts on the sides for yoke mounting give the DragonFly a range of deployment options. With a state of the art neodymium coaxial driver, the DragonFly is capable of producing highly intelligible audio at 122 dB SPL.

The DragonFly is highly expandable with an available expansion bay for use with Technomad's Schedulon audio player/recorder, a CD player module, a second wireless microphone or an audio distribution interface, including 900 Mhz wireless, ethernet and twisted pair configurations. Extended operation time is available through either internal or external battery pack options. Whether you need a self-contained, complete PA unit for field deployment or to expand or build an existing PA system with additional, compact output units, the DragonFly will exceed your expectations.

Technomad DragonFly PA System



Available Options

- · Schedulon audio player with scheduling capability
- Audio Distribution Modules:
 - Ethernet
 - Wireless (900Mhz)
 - · Twisted pair

- Multi day battery pack (external)
- Yoke-mount bracket
- · Additional wireless microphone
- · CD player module

Audio Performance Specifications

Frequency Response (+/- 2 dB) 90 Hz - 18 kHz Maximum Output (long term) 121 dB SPL Maximum Output (peak program) 124 dB SPL **HF Dispersion** 70°V x 70°H

All audio specifications based on ALMA EIA 426B test protocols.

General Specifications

Audio Outputs

Audio Inputs 1x XLR, mic. level 1x 1/4. line level 1x Mini XLR line out

AC power (90-240vAC) Power Inputs

Battery 5AH LiFeP0

Battery Operational Life 5+ hours full power op. 15+ hours stand-by

Physical Specifications

14.5 in. 36.8 cm Height Width 8.25 in. 20.9 cm Depth 14 in. 35.5 cm Weight 23 lb. 10.4 kg

Fittings:

Rigging points 2x 1/4-20 threaded inserts on top

(handle mount points) 2 x 1/4-20 threaded inserts on side Yoke mount points

Standmount sockets 1x 1.5" socket on bottom of unit Handles

1x strap handle

Mid-density Polyethylene Cabinet

Grill Multi-layer, high-impact polymer

w/ high RF transparency

Technomad Audio. Anywhere.

1x Neutrik NL4MP

DC power (12-24vDC)

5 Tina Drive, South Deerfield, MA 01373 email: customercare@technomad.com web: http://www.technomad.com phone: 800.464.7757 fax: 617 424 8233 international: +1.617.275.8898